



Trust-X® Double Reinforced Masonry Cut-off Wheels

- Provides fast economical cutting of masonry and fiberglass
- Designed to meet the demands of rough, heavy duty cutting operations under field conditions
- Ideal for cutting and keying of curbs, slabs, concrete and asphalt

SPECIFICATIONS

Grit Type..... Silicon Carbide



Code #	Diameter X Thickness	Center Mount	Max RPM	Tool
876-4-0700	7" X 1/8"	5/8" *	8,732	7" Circular Saw
876-4-1400	14" X 1/8"	1"	5,200	14" Gas Saw

* Diamond punch-out with 5/8" hole

Trust-X® Dia-Cut™ Concrete Grinding Wheels

- Contains proprietary diamond impregnated segments silver brazed to heat treated steel backing plate
- Engineered to be tough, aggressive and long lasting
- Single row wheels work best for concrete edge work and for keying the parameter of damaged areas
- Double row wheels work best for leveling concrete surface irregularities
- Use with Partsmaster Universal Dust Collection System and filtered shop vacuum for inside and confined area applications (See page 19)



Code #	Description
876-3-4601	4-1/2" X 5/8-11" Center Mount - Single-row, 8 Diamond Segments
876-3-4602	4-1/2" X 5/8-11" Center Mount - Double-row, 16 Diamond Segments