

Lubricants & Greases

FP-116™



GENERAL PURPOSE FOOD PLANT LUBRICANT

FP-116 food plant grease is specially formulated for food plant equipment. It is invisible, odorless, long-lasting, and it will not stain. FP-116 grease outperforms bulk greases and light bodied sprays. It will not sling off or break down, even in water, steam, or heavy load conditions.

- Specially formulated for food plant equipment
- Resists extreme pressure, corrosion and water washout
- White coloration for easy visual check
- High viscosity clings to vertical surfaces
- No sling off or break down even in watery, steamy conditions
- Wide temperature range -40°F to 550°F

Specifications

Color Creamy white
 Odor Petroleum
 Flammability Extremely flammable
 Temperature range -40°F to 550°F
 (-40°C to 288°C)
 Solubility Insoluble in water

For food plant usage see page 80; guideline #4

Code #	Size	Description
600-2-5032	10 oz. / 283 g	Case of 12
900-1-0051	10 oz. / 283 g	4-Pack

GEAR GUARD™



OPEN GEAR LUBRICANT

Gear Guard open gear lubricant is a tar based multipurpose aerosol lubricant. This thick tacky solid film lubrication stays where it is applied even when oil is forced off. It is effective under watery or in hot, steamy conditions. It will not drip, sling off, melt, dry out, or build up between gear teeth. Gear Guard lubricant grease lasts longer than standard open gear lubricants.

- Provides a solid film lubricant when other materials are forced off
- Special formula allows product to stretch ensuring contact on surfaces
- Protects against rust and corrosion by repelling moisture
- Extends machinery life as well as helps reduce noise

Specifications

Color Black
 Odor Solvent
 Flammability Flammable
 Temperature range 20°F to 175°F
 (-6°C to 79°C)

For food plant usage see page 80; guideline #5

Code #	Size	Description
600-2-5623	12 oz. / 340 g	Case of 12
900-1-0039	12 oz. / 340 g	4-Pack