



Scan to see video!

DOD EMALL
<https://dod.emall.dla.mil>
 SP47W1-17-D-0009
 Available in select sizes only



Straight Flute Screw Extractors

Fabricated from tool steel with a lacquer-based surface treatment to resist rust and tarnish. The sharp, straight, tapered flute bites into the work without binding or chewing. Removes right and left threads on bolts, screws, pipes and studs.

SPECIFICATIONS

Material AISI 1095 tempered steel
 Hardness 54-58 Rc

Code #	Extractor Number	To Remove	Drill Size
805-0-6151	1	1/4"-5/16"	1/8"
805-0-6152	2	3/8"	3/16"
805-0-6153	3	7/16"	13/64"
805-0-6154	4	1/2"-9/16"	5/16"
805-0-6155	5	5/8"	3/8"

Assortments

- 999-0-6262 5 piece - Straight Flute Set
1 each - #1, #2, #3, #4, and #5
- 999-0-0010 10 piece - Straight Flute Screw Extractors and Cryobits 5
Cryobits- 1/8", 3/16", 5/16", 13/64", and 3/8"
Straight Flute Screw Extractor - #1, #2, #3, #4, and #5
- 999-6-2805 10 piece - Straight Flute Screw Extractors with
Left-handed Cryobits
5 Left Hand Cryobits - 1/8", 3/16", 1/4", 5/16", and 3/8"
Straight Flute Screw Extractor #1, #2, #3, #4, and #5
- 999-6-2806 15 piece - Straight Flute Screw Extractors, Left-Handed
Drill Bit and Bolt Planing Burr Set
Contains items in 999-6-2805 and #1 -5 Cryo-Burr Bolt
Planing Burrs
- 999-6-2804 15 piece - Straight Flute Screw Extractors, Left-Handed
Drill Bit and Bolt Planing Burr Set
Contains items in 999-6-2805 plus #1 -5 Cryo-Burr Bolt
Planing Burrs with Adjustable Tray

Sets Includes Includes Straight Flute Screw Extractor, Left-Hand Drill Bit and Cryo-Burr Bolt Top Planning Burr

Code #	To Remove
832-2-0501	1/4" USS / SAE, 7mm
832-2-0502	5/16" USS / SAE, 8mm
832-2-0503	3/8" SAE
832-2-0504	3/8" USS
832-2-0505	7/16" USS / SAE, 10mm
832-2-0506	1/2"-9/16" USS / SAE, 12mm - 14mm
832-2-0507	5/8" USS / SAE, 16mm - 20mm