



SDS+ / Carbide Hammer Drills Shank

These carbide hammer drill bits have tough tungsten carbide tips that are brazed into place for durability and long life. The tungsten will stay sharper longer for more drilling from each bit. The special asymmetrical spiral and undercut fluting is designed to clear debris quickly without raising a dust cloud. The bits have steel bodies that are annealed to increase flexibility and reduce brittleness. They are shot peened to tension the surface and protect against twisting and torquing. Use these bits for drilling in concrete, brick, stone, marble and other masonry materials. They fit all rotary hammers with SDS-Plus chucks. Use Quick Change Adapters (p.21) to adapt SDS-Plus bits to Spline or SDS-Max chucks.

SPECIFICATIONS

Drill Motor Fits rotary hammers with SDS-Plus chucks
 Material..... Hardened tool steel with tungsten carbide tip and annealed shaft

Code#	Diameter	Usable Length	Overall Length
804-4-0804	5/32"	4"	6"
804-4-0904	3/16"	2"	4"
804-4-0906	3/16"	4"	6"
804-4-0908	3/16"	6"	8"
804-4-0910	3/16"	8"	10"
804-4-0912	3/16"	10"	12"
804-4-0914	3/16"	12"	14"
804-4-0916	3/16"	14"	16"
804-4-1106	7/32"	4"	6"
804-4-1108	7/32"	6-1/2"	8-1/2"
804-4-1110	7/32"	10-1/2"	10-1/2"
804-4-1304	1/4"	2"	4"
804-4-1306	1/4"	4"	6"
804-4-1308	1/4"	6"	8"
804-4-1310	1/4"	8"	10"
804-4-1312	1/4"	10"	12"
804-4-1314	1/4"	12"	14"
804-4-1706	5/16"	4"	6"
804-4-1712	5/16"	10"	12"
804-4-2106	3/8"	4"	6"
804-4-2110	3/8"	8"	10"
804-4-2112	3/8"	10"	12"
804-4-2118	3/8"	16"	18"
804-4-2506	7/16"	4"	6"
804-4-2512	7/16"	10"	12"
804-4-2518	7/16"	16"	18"
804-4-2906	1/2"	4"	6"
804-4-2910	1/2"	8"	10"
804-4-2912	1/2"	10"	12"
804-4-2918	1/2"	16"	18"
804-4-2924	1/2"	22"	24"
804-4-3006	9/16"	4"	6"
804-4-3012	9/16"	10"	12"
804-4-3106	5/8"	4"	6"
804-4-3108	5/8"	6"	8"
804-4-3112	5/8"	10"	12"
804-4-3118	5/8"	16"	18"
804-4-3308	3/4"	6"	8"
804-4-3312	3/4"	10"	12"
804-4-3318	3/4"	16"	18"
804-4-3508	7/8"	6"	8"
804-4-3512	7/8"	10"	12"
804-4-3518	7/8"	16"	18"
804-4-3710	1"	8"	10"
804-4-3718	1"	16"	18"



Code #	Description
804-4-0000	7 pc. Metal Index 1 ea - 3/16" X 4, 1/4" X 4, 5/16" X 6, 3/8" X 6, 1/2" X 6, 2 ea - 1/4" X 6



SDS+ Bits for Mas-Tap™

The SDS-Plus Hex Anchor Drive Bits can be used in conjunction with the Partsmaster Mas-Tap™ tool (800-0-1901), or other common concrete screw anchor installation tools. The Mas-Tap™ tool slides over the bit and snaps onto the hex at the base of the bit. This allows the user to produce holes with SDS-Plus hammer drill speed and then quickly drive the Mas-Tap Concrete anchor.

SDS+ Drill Bit and Tool Adapters



The SDS-Plus Quick Change Adapters allow you to use SDS-Plus Hammer Bits on drills with Spline or SDS-Max chucks. Simply chuck the adapter into the hammer drill, and the SDS hammer bits easily snap in and out of the Quick Change collet.

SPECIFICALLY DESIGNED SDS+ FOR USE WITH MAS-TAP

INSTALLATION TOOL, CODE # 800-0-1901

804-4-5605	5/32 X 5	3"	5"
804-4-5606	5/32 X 6	4"	6"
804-4-5607	5/32 X 7	5"	7"
804-4-5905	3/16 X 5	3"	5"
804-4-5906	3/16 X 6	4"	6"

STYLE CHUCK TO CONVERT TO SDS+

Code #	Overall Length
804-4-0001	Spline Chuck 8-1/4"
804-4-0002	SDS-MAX™ Chuck 8-1/4"



Available in select sizes only