



T-Bit™ Threaded Shank Drill System

- Enables standard drill motors to reach into areas with at least 2" of clearance
- Provides easy access to hard-to-reach areas
- Can be used with flex shaft snakes and right angle tool for drilling in tight spaces, extending a drill bit for more reach, or using small abrasives to grind, cut, sand or brush
- Drill bits meet the latest NAS 907 aircraft standards and are Cryophase™ treated for maximum life and durability

SPECIFICATIONS

Material Aircraft quality Molybdenum tool steel
 Hardness 63-65 Rc
 Aircraft Specifications..... Meets NAS 907
 Cryophase Patented thermal cycling cryogenic process

Size	Shank Length		
	Long 2-1/8"	Short 1-1/4"	Stubby 9/16"
3/32"	808-1-0300	808-2-0300	000-4-0303
1/8"	808-1-0500	808-2-0500	-
5/32"	808-1-0700	808-2-0700	-
3/16"	808-1-0900	808-2-0900	-
7/32"	808-1-1100	808-2-1100	000-4-0311
1/4"	808-1-1300	808-2-1300	-
#40	808-1-0040	808-2-0040	808-3-0040
#30	808-1-0030	808-2-0030	808-3-0030
#27	808-1-0027	808-2-0027	808-3-0027
#21	808-1-0021	808-2-0021	808-3-0021
#20	808-1-0020	808-2-0020	000-4-0420
#13	808-1-0013	808-2-0013	000-4-0413
#11	808-1-0011	808-2-0011	808-3-0011
#10	808-1-0010	808-2-0010	808-3-0010



Available in select sizes only



000-Series numbers are non-stocking

- 808-4-5010 Long - Numbered & Fractional
10 pc 3/32, 1/8, 5/32, 3/16, 7/32, 1/4, #40, #30, #27, #10
- 808-4-5012 Short - Fractional and Short & Stubby Numbered
13 pc: Short - 3/32, 1/8, 5/32, 3/16, 1/4, #10, #21, #30, #40
Stubby - #10, #21, #30, #40
- 999-8-1425 General Maintenance Short T-Bit with Tray
Short - 3/32, 1/8, 5/32, 3/16, 7/32, 1/4, #10, #20, #30, #40, #2 PH, #3-4 Slotted, Wrench, 6" Extension, Right Angle Tool
- 991-3-1425 General Maintenance Tray Refill
Short T-Bits - 3/32, 1/8, 5/32, 3/16, 7/32, 1/4, #10, #20, #30, #40