

**DOD EMALL**  
<https://dod.emall.dla.mil>  
 SPMLW1-13-D-E098  
 Available in select sizes only



**SPECIFICATIONS**

RPM Max..... 2500

**CLEARANCE**

With Long T-Bit - 3-1/2" , With Short T-Bit - 2-1/2" With Stubby T-Bit-2"

**T-Bit™ Right Angle Tool**

Use the T-Bit Right Angle Tool with the T-Bit Drill Bits to make repairs quickly and easily without disassembling equipment. The rust-free nylon housing and knurled aluminum sleeve provide strength and insulation while damping vibration. In addition, the tool can be used with screwdriver bits, brushes and extensions for a longer reach.

Code #	Description
808-4-0100	1/4" shaft, 1/4-28 thread; 8" length

**DOD EMALL**  
<https://dod.emall.dla.mil>  
 SPMLW1-13-D-E098  
 Available in select sizes only

800-0-0722,0730



800-0-0690



800-0-0740

**T-Bit Snakes**

T-Bit Snakes attach to a standard drill motor to allow for optimum reach in difficult places. They are constructed of reinforced flexible steel casings with a 4-ply synthetic rubber core.

**SPECIFICATIONS**

RPM Max..... 2500

Code #	Description
800-0-0722	Straight Head, 1/4-28 Thread, 22" Length
800-0-0730	Straight Head, 1/4-28 Thread, 30" Length
800-0-0690	90° Head, 1/4-28 Thread, 30" Length
800-0-0740	Straight Head, Adjustable Chuck, 52" Length 1/16"-5/16" bits (NOTE: not a threaded collet, use with standard bits or chucking spud)

**DOD EMALL**  
<https://dod.emall.dla.mil>  
 SPMLW1-13-D-E098  
 Available in select sizes only



\* 9" Extension has 1/4" Shank for use in standard drill motors.

**T-Bit Extensions**

Use with the T-Bit Right Angle Tool or Snakes for reaching 3", 6", 9" or use in combination for additional options.

Code #	Description
808-4-0030	3" extension
808-4-0060	6" extension
808-4-0090	9" extension*

**DOD EMALL**  
<https://dod.emall.dla.mil>  
 SPMLW1-13-D-E098  
 Available in select sizes only



**Installation Drivers for T-Bit Tool**

Threaded drivers specially designed for direct placement into the T-Bit tool.

Code #	Description
808-4-0001	#1 Phillips Driver 1/4"-28 thread
808-4-0002	#2 Phillips Driver 1/4"-28 thread
808-4-0003	#3-4 Slotted Driver 1/4"-28 thread
808-4-0004	#6-8 Slotted Driver 1/4"-28 thread