

Code #	Description
808-4-1501	3/8" Double end cutter
808-4-1502	1/4" hex Arbor with tension adjustment
808-4-1503	Ejector pin
808-4-1500	CryoSpotWeld Kit – includes 1 ea. all items listed above



SPECIFICATIONS

Material.....Cryophase™ treated high speed steel
 Cutter Diameter.....3/8"
 Arbor 1/4" hex shank x 2-3/8" long (with out pilot tip)
 Pilot tip (comes with arbor) Hardened alloy steel



Available in select sizes only

CryoSpotWeld™ Bit

The Fastest Way to Remove Spot Welds

- **Depth Control** – Built-in pilot spring in the arbor can be adjusted to control depth
- **More Holes** – Cutter is double-ended for twice the tool life
- **Longer Lasting** – Cryophase™ treatment makes the cutting edge more wear resistant and faster cutting

Code #	Size	Thread Size
818-2-3700	1"	1/2"-20
818-2-3800	1-1/8"	1/2"-20
818-2-3900	1-1/4"	5/8"-18
818-2-4000	1-3/8"	5/8"-18
818-2-4100	1-1/2"	5/8"-18
818-2-4300	1-3/4"	5/8"-18
818-2-4500	2"	5/8"-18

Carb-Cut™ Tungsten Carbide Hole Saws

- Feature extra-hard tungsten carbide particles bonded to tough alloy steel to provide hundreds of virtually indestructible cutting surfaces
- Carb-Cut™ hole saws will cut through almost any material without breaking, including masonry, fiberglass, ceramic tile, composition board, and plastics

Note: Arbors and pilot drills sold separately.

Arbors and Pilot Drills

Code #	Shank (Chuck) Size	Thread Connection	Drill Bit Code#		Arbor
			Masonry	Percussion	
818-1-0033	1/4" (1/4")	1/2"-20	804-1-1753	804-3-1353	818-1-0044
818-1-0034	5/16" (3/8")	1/2"-20	804-1-1753	804-3-1353	818-1-0044
818-1-0044	7/16" (1/2")	1/2"-20	804-1-1753	804-3-1353	818-1-0044
818-1-0055	7/16" (1/2")	5/8"-18	804-1-1753	804-3-1353	818-1-0055



Available in select sizes only