

## Partsmaster 1/2" Reduced Shank Drill Bits

- Available in 64<sup>th</sup> inch increments to 1" and popular sizes up to 1-1/2"
- Manufactured from molybdenum high speed tool steel for long life
- 1/2" reduced shank with flats - can be used in keyed or keyless chucks without slipping
- Silver with black-oxide flutes to hold lubricant at the cutting surface
- 118° point for fast cutting
- Available in an eight piece assortment for sizes 9/16" to 1" in 1/16" increments



### Applications:

Steel	Aluminum	Cast Steel
Copper	Brass	Malleable Iron
Bronze	Cast Iron	

### Specifications:

Material.....	Molybdenum high speed steel
Finish .....	Silver and black oxide
Point .....	118° standard
Over-all length .....	6"
Max. depth of cut.....	2.1"
Length of flats on shank.....	1"
Shank diameter .....	1/2"

*Note: A pilot hole is recommended when using PM Reduced Shank Bits*

Code #	Size	Code #	Size
082-0-0355	33/64"	082-0-0365	43/64"
082-0-0356	17/32"	082-0-0366	11/16"
082-0-0357	35/64"	082-0-0367	45/64"
082-0-0358	9/16"	082-0-0368	23/32"
082-0-0359	37/64"	082-0-0369	47/64"
082-0-0360	19/32"	082-0-0370	3/4"
082-0-0361	39/64"	082-0-0371	49/64"
082-0-0362	5/8"	082-0-0372	25/32"
082-0-0363	41/64"	082-0-0373	51/64"
082-0-0364	21/32"	082-0-0374	13/16"

**Code #****Size**

082-0-0375	53/64"
082-0-0376	27/32"
082-0-0377	55/64"
082-0-0378	7/8"
082-0-0379	57/64"
082-0-0380	29/32"
082-0-0381	59/64"
082-0-0382	15/16"
082-0-0383	61/64"
082-0-0384	31/32"
082-0-0385	63/64"
082-0-0386	1"

**Code #****Size**

082-0-0387	1-1/32"
082-0-0388	1-1/16"
082-0-0389	1-3/32"
082-0-0390	1-1/8"
082-0-0391	1-5/32"
082-0-0392	1-3/16"
082-0-0393	1-7/32"
082-0-0394	1-1/4"
082-0-0395	1-5/16"
082-0-0396	1-3/8"
082-0-0397	1-1/2"

**Assortment**

082-0-0350	8pc asst. 9/16" to 1"
------------	-----------------------