

Grade 8 Hex Head Cap Screws (continued)

FEDMALL
SP47W1-17-D-0009
Available in select sizes only

Length	1/2"-13 USS	1/2"-20 SAE	9/16"-12 USS	9/16"-18 SAE	5/8"-11 USS	5/8"-18 SAE	3/4"-10 USS	3/4"-16 SAE	Length
3/4"	005-2-2933	005-1-2933	-	-	-	-	-	-	3/4"
7/8"	005-2-2935	005-1-2935	-	-	-	-	-	-	7/8"
1"	005-2-2937	005-1-2937	005-2-3037	005-1-3037	005-2-3137	005-1-3137	005-2-3337	005-1-3337	1"
1-1/4"	005-2-2939	005-1-2939	005-2-3039	005-1-3039	005-2-3139	005-1-3139	005-2-3339	005-1-3339	1-1/4"
1-1/2"	005-2-2941	005-1-2941	005-2-3041	005-1-3041	005-2-3141	005-1-3141	005-2-3341	005-1-3341	1-1/2"
1-3/4"	005-2-2943	005-1-2943	005-2-3043	005-1-3043	005-2-3143	005-1-3143	005-2-3343	005-1-3343	1-3/4"
2"	005-2-2945	005-1-2945	005-2-3045	005-1-3045	005-2-3145	005-1-3145	005-2-3345	005-1-3345	2"
2-1/4"	005-2-2946	005-1-2946	005-2-3046	005-1-3046	005-2-3146	005-1-3146	005-2-3346	005-1-3346	2-1/4"
2-1/2"	005-2-2947	005-1-2947	005-2-3047	005-1-3047	005-2-3147	005-1-3147	005-2-3347	005-1-3347	2-1/2"
2-3/4"	005-2-2948	005-1-2948	005-2-3048	005-1-3048	005-2-3148	005-1-3148	005-2-3348	005-1-3348	2-3/4"
3"	005-2-2949	005-1-2949	005-2-3049	005-1-3049	005-2-3149	005-1-3149	005-2-3349	005-1-3349	3"
3-1/4"	005-2-2950	005-1-2950	005-2-3050	005-1-3050	005-2-3150	005-1-3150	005-2-3350	005-1-3350	3-1/4"
3-1/2"	005-2-2951	005-1-2951	005-2-3051	005-1-3051	005-2-3151	005-1-3151	005-2-3351	005-1-3351	3-1/2"
3-3/4"	005-2-2952	005-1-2952	005-2-3052	005-1-3052	005-2-3152	005-1-3152	005-2-3352	005-1-3352	3-3/4"
4"	005-2-2953	005-1-2953	005-2-3053	005-1-3053	005-2-3153	005-1-3153	005-2-3353	005-1-3353	4"
4-1/2"	005-2-2955	005-1-2955	005-2-3055	005-1-3055	005-2-3155	005-1-3155	005-2-3355	005-1-3355	4-1/2"
5"	005-2-2957	005-1-2957	005-2-3057	005-1-3057	005-2-3157	005-1-3157	005-2-3357	005-1-3357	5"
5-1/2"	005-2-2959	005-1-2959	005-2-3059	005-1-3059	005-2-3159	005-1-3159	005-2-3359	005-1-3359	5-1/2"
6"	005-2-2961	005-1-2961	005-2-3061	005-1-3061	005-2-3161	005-1-3161	005-2-3361	005-1-3361	6"
6-1/2"	005-2-2963	-	-	-	005-2-3163	-	005-2-3363	-	6-1/2"
7"	005-2-2965	005-1-2965	005-2-3065	-	005-2-3165	005-1-3165	005-2-3365	005-1-3365	7"
8"	005-2-2969	005-1-2969	005-2-3069	-	005-2-3169	005-1-3169	005-1-3369	005-1-3369	8"
9"	005-2-2973	-	-	-	005-2-3173	-	005-2-3373	-	9"
10"	-	-	-	-	005-2-3177	-	005-2-3377	-	10"

Length	7/8"-9 USS	7/8"-14 SAE	1"-8 USS	1"-14 SAE	1-1/8"-7 USS	1-1/4"-7 USS	Length
1-1/2"	005-2-3541	005-1-3541	005-2-3741	-	-	-	1-1/2"
2"	005-2-3545	005-1-3545	005-2-3745	005-1-3745	-	-	2"
2-1/4"	005-2-3546	005-1-3546	005-2-3746	005-1-3746	-	-	2-1/4"
2-1/2"	005-2-3547	005-1-3547	005-2-3747	005-1-3747	005-2-3947	-	2-1/2"
2-3/4"	005-2-3548	005-1-3548	005-2-3748	005-1-3748	-	-	2-3/4"
3"	005-2-3549	-	005-2-3749	005-1-3749	005-2-3949	005-2-4149	3"
3-1/4"	005-2-3550	005-1-3550	005-2-3750	005-1-3750	-	-	3-1/4"
3-1/2"	005-2-3551	005-1-3551	005-2-3751	005-1-3751	005-2-3951	005-2-4151	3-1/2"
3-3/4"	005-2-3552	005-1-3552	005-2-3752	-	-	-	3-3/4"
4"	005-2-3553	005-1-3553	005-2-3753	005-1-3753	005-2-3953	005-2-4153	4"
4-1/2"	005-2-3555	005-1-3555	005-2-3755	005-1-3755	-	005-2-4155	4-1/2"
5"	005-2-3557	005-1-3557	005-2-3757	005-1-3757	005-2-3957	005-2-4157	5"
5-1/2"	005-2-3559	005-1-3559	005-2-3759	005-1-3759	005-2-3959	005-2-4159	5-1/2"
6"	005-2-3561	005-1-3561	005-2-3761	005-1-3761	005-2-3961	005-2-4161	6"
6-1/2"	005-2-3563	-	005-2-3763	-	-	-	6-1/2"
7"	005-2-3565	-	005-2-3765	005-1-3765	005-2-3965	005-2-4165	7"
8"	005-2-3569	-	005-2-3769	005-1-3769	-	005-2-4169	8"
9"	005-2-3573	-	005-2-3773	-	-	005-2-4173	9"
10"	005-2-3577	-	005-2-3777	-	-	005-2-4177	10"

Grade 8 Hex Nuts


- Standard Grade 8 nuts for Grade 8 cap screws and other high strength fasteners
- Dy-Cro-Sist™ plated for maximum corrosion on resistance

SPECIFICATIONS	
Hardness.....	24-32 Rc (1/4" to 5/8"); 26-34 Rc (9/16" to 1-1/2")
Minimum Proof Load.....	150,000 psi
Approvals.....	Meets ANSI/ASME B18.2.2; SAE J995
Plating.....	Dy-Cro-Sist™ plated and baked to relieve hydrogen embrittlement

Size	USS	SAE
1/4"	019-8-1300	019-7-1300
5/16"	019-8-1700	019-7-1700
3/8"	019-8-2100	019-7-2100
7/16"	019-8-2500	019-7-2500
1/2"	019-8-2900	019-7-2900

Size	USS	SAE
9/16"	019-8-3000	019-7-3000
5/8"	019-8-3100	019-7-3100
3/4"	019-8-3300	019-7-3300
7/8"	019-8-3500	019-7-3500
1"	019-8-3700	019-7-3700

Size	USS	SAE
1-1/8"	019-8-3900	019-7-3000
1-1/4"	019-8-4000	019-7-4000
1-1/2"	019-8-4200	019-7-4200




High Strength/High Profile Nuts Proprietary Grade

- For use with Dynamark, F-911, L-9, Six Shooter and Grade 8 cap screws or when higher strength is needed
- Provides increased thread engagement for added gripping to cap screw threads
- Dy-Cro-Sist™ plated and fully traceable by lot number

SPECIFICATIONS	
Hardness.....	32-38 Rc
Plating.....	Dy-Cro-Sist™
Approvals.....	Exceeds SAE Grade 8, ANSI/ASME B18.2.2
Proof Load.....	180,000 psi

Size	USS	SAE
1/4"	020-4-1300	020-3-1300
5/16"	020-4-1700	020-3-1700
3/8"	020-4-2100	020-3-2100
7/16"	020-4-2500	020-3-2500*
1/2"	020-4-2900	020-3-2900*

Size	USS	SAE
9/16"	020-4-3000*	020-3-3000*
5/8"	020-4-3100*	020-3-3100*
3/4"	020-4-3300*	020-3-3300*
7/8"	020-4-3500*	020-3-3500*
1"	020-4-3700*	-



*Dyna Systems reserves the right to substitute nuts on certain sizes with low usage, with product of equal strength and specifications. All substitutions are lot traceable, made in U.S.A., and backed by the Dyna Systems multi-million dollar liability policy.